




## 1.0 LED

LED 8W | 220-240VAC | 50-60Hz  
COB2-step | incl. PS | phase-cut dim


CE 0.67kg TE 960° IP20  $\lambda$ 0,3  $\lambda$ 36°



## 1.0 PAR16

PAR16 max. 50W | GU10  
220-240VAC | 50-60Hz

CE 0.66kg TE 960° IP20  $\lambda$ 0,9  $\lambda$ 36°



2200K | >80CRI | 315lm

	<b>146164G1</b>
	<b>146164Q1</b>
	<b>146164B1</b>

2700K | >80CRI | 480lm

	<b>146164W2</b>
	<b>146164L2</b>
	<b>146164G2</b>
	<b>146164Q2</b>
	<b>146164B2</b>

3000K | >80CRI | 480lm

	<b>146164W4</b>
	<b>146164L4</b>
	<b>146164G4</b>
	<b>146164Q4</b>
	<b>146164B4</b>

	<b>146120W0</b>
	<b>146120L0</b>
	<b>146120G0</b>
	<b>146120Q0</b>
	<b>146120B0</b>

### OPTIONAL

PAR16 LED GU10 6W phase-cut dim  
2700K 390lm **901228W2**

3000K 410lm **901228W4**

PAR16 LED GU10 7W ambient white dim  
1800-3000K **901229S9**



### OPTIONAL

inner cover

	<b>911011W1</b>
	<b>911011G1</b>
	<b>911011B1</b>

