

SHAPE



design K.Begasse



reddot award 2014
winner

Shape



www.simes.it/shape



SHAPE

surfaced mounted accent lighting

Die-cast EN AB-47100 aluminium (low copper content) housing with high corrosion resistance.
 Protective Cover with clip locking system.
 No visible screws.
 Clear polycarbonate diffuser.
 Supplied with a 1,5m pre-wired H05RN-F cable.
 Silicone gaskets.

Double powdered paint in 3 step process:
 _ surface treatment containing ceramic nano particles (Bonderite);
 _ epoxy primer paint;
 _ polyester powder paint with high resistance against UV rays and harsh weather conditions.

The fitting allows an adjustment of approximately 5° for the perfect alignment of the light beam with the window frame.

Colours:

- White (code 01)
- Aluminium grey (code 14)

Protection class
 IP65

Isolation class
 CLASS I ⚡ SHAPE
 CLASS III ⚡ MINISHAPE

Mechanical resistance of diffuser
 IK 10

Luminaires supplied with LED circuit board.

This luminaire contains built-in LED modules with energy class:

A A+ A++

The LED modules cannot be changed in the luminaire (Regulation UE 874/2012).

For updated data, see technical sheets and installation instructions available on our website (www.simes.com).

Accessories for Minishape

S.3424

REMOTE FIXED-POWER SUPPLY
230V/1200mA
 Power consumption 6W
 Dimensions 57mm x31mm x21mm
IP20



Must be installed in protect area, suitable for 1 device.

S.3423


REMOTE MULTI-POWER SUPPLY
230V/350mA-1000mA
 Dimmable 1-10V, PUSH BOTTON
 Maximum power consumption:
 at 350mA 15W
 at 1000mA 39W
 Dimensions 130mm x67mm x21mm
IP20



For easy installation we recommend the wiring of maximum 2 devices in series to each power supply.




MINI-SHAPE




S.6425W

With led white 3000K CRI80
 Rated input power 1,0W-350mA ÷ 3,6W-1200mA
 With radial lens 10°x170°
 Requires remote power supply 230V/**350mA-1000mA** (type S.3423)
 or remote power supply 230V/**1200mA** (type S.3424)



S.6425N


With led white 4000K CRI70
 Rated input power 1,0W-350mA ÷ 3,6W-1200mA
 With radial lens 10°x170°
 Requires remote power supply 230V/**350mA-1000mA** (type S.3423)
 or remote power supply 230V/**1200mA** (type S.3424)



mA	350	500	700	900	1000	1200
Watt	1,0	1,5	2,1	2,7	2,9	3,6
lumen (3000K)	80	91	102	114	122	151
lumen (4000K)	85	105	125	146	156	200




SHAPE



S.6420W

With led white 3000K CRI80 350lm
 Rated luminaire luminous flux 151lm
 Rated input power 4,7W 240V
 With radial lens 10°x170°



S.6420N

With led white 4000K CRI70 400lm
 Rated luminaire luminous flux 200lm
 Rated input power 4,7W 240V
 With radial lens 10°x170°

