

Trimless SCT





SCTLED 200

LED

- 1-, 2- or 3-lamp recessed spotlight with LED technique for general lighting, fitting suitable for reflector lamps LED AR 111/GU10
- for recess flush with ceiling into plasterboard for trimless integration to modern architecture
- light heads flexible rotatable and pivotable
- tool-free maintenance
- energy saving, no UV and thermal emissions,

- perfect thermal management
- ready for 230 V AC connection
- LED lamps to be ordered separately
- colour: silver, black, white
- on request also available as dimming version
- Data based at the time of printing. For latest information click on www.lts-light.eu

Recessed spotlights | Trimless | LED AR111

CRI > 80




IP20



Light source LED AR111/GU10

Plasterboard

- easy drywall mounting
- adjustable for different ceiling thickness
- mounting frame made from aluminium, with plaster edge (included)



ET			DS	kg	Order No.
155	154×154	156×156	12.5-26.5	1.1	SCTLED 201.1110



155	282×154	285×156	12.5-26.5	1.6	SCTLED 202.1110
-----	---------	---------	-----------	-----	---------------------------------



155	410×154	413×156	12.5-26.5	2.2	SCTLED 203.1110
-----	---------	---------	-----------	-----	---------------------------------

SCT 200 System



LED

- recessed spotlight in 1- to 4-lamp design for recess flush with ceiling in plasterboard
- mounting frames and light heads assembled in factory
- light heads move in all directions on gimbals
- thermal management with passive cooling or ultra quiet active cooling
- energy saving, no UV and thermal emissions
- specular reflectors made from high-quality aluminium in PRI Plus technique for glare-free light and maximum luminous efficiency

- ready to plug-in to ballast
- **mounting frames and light heads including casting surrounds to be ordered separately**
- ballast included
- colour: silver, black, white
- on request also available as dimming version and/or with CRI > 90
- Data based at the time of printing. For latest information click on www.lts-light.eu

Recessed spotlights | Trimless | system | LED



CRI > 80



15° - 45°




PRI PLUS



safety glass

Mounting frame

f	ET	DS	kg	Order No.
1-lamp				
176×166	140	8-16	2.0	SCT 201.00
2-lamp				
328×166	140	8-16	3.1	SCT 202.00
3-lamp				
480×166	140	8-16	4.1	SCT 203.00
4-lamp				
632×166	140	8-16	5.1	SCT 204.00



Accessories

Honeycomb louvre black [ZBW 20](#)

Plasterboard

- easy mounting of the ceiling installation frame with drywall screws
- mounting frame made from aluminium, with plaster edge
- adjustable for different ceiling thickness

Light head LED

LM	System power	Lumen	Beam angle	Color temperature	Order No.	
with passive cooling						
☒ LED	27 W	> 2000 lm	15°	2700 K	SCEKLP 200.2027.15	
				3000 K	SCEKLP 200.2030.15	
				4000 K	SCEKLP 200.2040.15	
☒ LED	37 W	> 2700 lm	15°	2700 K	SCEKLP 200.3027.15	
				2700 K	SCEKLP 200.3030.15	
				2700 K	SCEKLP 200.3040.15	
				25°	2700 K	SCEKLP 200.3027.25
				3000 K	SCEKLP 200.3030.25	
				4000 K	SCEKLP 200.3040.25	
☒ LED	37 W	> 2700 lm	15°	2700 K	SCEKLP 200.3027.35	
				3000 K	SCEKLP 200.3030.35	
				4000 K	SCEKLP 200.3040.35	
				25°	2700 K	SCEKLP 200.3027.25
				3000 K	SCEKLP 200.3030.25	
				4000 K	SCEKLP 200.3040.25	
☒ LED	37 W	> 2700 lm	15°	2700 K	SCEKLP 200.3027.45	
				3000 K	SCEKLP 200.3030.45	
				4000 K	SCEKLP 200.3040.45	
				25°	2700 K	SCEKLP 200.3027.25
				3000 K	SCEKLP 200.3030.25	
				4000 K	SCEKLP 200.3040.25	