



- Housing:** made of sheet steel.
- Reflector:** high luminous efficiency 99.99 frosted aluminium.
- Dark light louvre:** double parabolic louvres, in matt 99.99 aluminium, anti-glare and anti-iridescence, very low luminance, PVD treatment to improve luminous efficiency.
- Coating:** housing acrylic anionic electrocoating, UV-stabilized.
- Equipment:** 3,15A protection fuse. Supplied with 1.5m cable with plug.

WATTAGE traditional T5	CONSUMPTION lamps supplied
54W	50W
The fixtures with T5 lamps are supplied as standard with energy saving lamps.	

916 Ibis T5 - matt optical 99,99						
		CELL-F		CELLF-E		Lamps (Ta=25°C)
wattage	colour	weight	code	weight	code	Kelvin - ølm - Ra
FL 2x24	white	4.80	154010-00	5.50	154010-07	4000K - 1750lm - Ra 1b
FL 2x28	white	7.50	154011-00	8.20	154011-07	4000K - 2650lm - Ra 1b
FL 2x54	white	7.50	154012-00	8.40	154012-07	4000K - 4450lm - Ra 1b
FLC 2x55L	white	4.80	154013-00			4000K - 4800lm - Ra 1b

**On request:** versions with DIM 1-10V wiring (dimmable 1-10V), DIMDIG (digital dimming). On request: EM version with 3 hour duration. **Supplied without brackets:** when not contact mounted, use brackets acc. 900. See page 30.

- EL A2
- EM
- DIMM DIG
- A1 DIMM
- MAIN CONTROL SYSTEM
-